SV-BA401-E IP camera Data Sheet

- Built-in microSD slot
- Built-in microphone
- Metal casing
- Support for PoE
- IR illumination up to 30 m
- Configuration via web interface
- ONVIF



Integrated networking solutions

**SV-BA401-E** wired IP camera with a cylindrical design provides a horizontal viewing angle of 100° and is equipped with a 4 MP CMOS matrix for clear video with a resolution of up to  $2560 \times 1440$ . The device has a night shooting mode (IR illumination), motion detection system and the function of saving the video archive to a memory card or network storage<sup>1</sup>. The camera is equipped with an RJ-45 connector with support for basic network protocols.

#### **Technical features**

	Interfaces	
Ethernet	1 × 10/100BASE-T (RJ-45), support for PoE	
Memory card	1 × MicroSD/SDHC/SDXC up to 128 GB	
Operating system		
Linux SDK		
	Sensor	
Туре	1/3" progressive scan CMOS	
Effective pixels	4M	
Lens and illumination		
Focal distance	2.8 mm	
Aperture	F/2.0	
Field of view (horizontal)	100°	
Field of view (diagonal)	116°	
Angle adjustment (tilt)	from 0° to 90°	
Angle adjustment (rotate)	from 0° to 360°	
IR illumination	yes	
IR range	up to 30 m	
Image		
Maximum resolution	2560 × 1440	
Maximum frame rate	25 fps	
Bit rate	up to 10 Mbps	
Video compression	H.264, H.265	
Image quality improvement	BLC, HLC, DWDR, ANTI-FLICKER	
Signal-to-noise ratio	no less that 50 dB	
Minimum illumination	color: 0.03 lx, bw: 0 lx with IR	

<sup>1</sup> Under development.



# **Technical features (continued)**

Audio	
Built-in microphone	yes
Built-in dynamic	no
Audio compression	PCM, AAC, MP2
Voice pickup distance	up to 5 m
	Physical specifications
Power supply	12 B DC, PoE 802.3af
RAM	128 MB
ROM	32 MB
Casing	metal
Form factor	cylindrical camera
Mount options	indoor and outdoor
Dimensions (W $\times$ H $\times$ D)	70 × 67 × 186 mm
Weight	0.38 kg
Operating temperature	from -40 to +60 °C
Operating humidity	no more than 90 % (non-condensing)
Ingress Protection	IP67

## **Analytics and protocols<sup>1</sup>**

- Motion detection
- Line crossing detection
- Perimeter intrusion detection

## Features and capabilities

- Night vision
- Storage: memory card, network storage<sup>1</sup>
- Management via web interface
- Non-volatile time (up to 24 hours)

## **Ordering information**

Name	Description	
SV-BA401-E	SV-BA401-E wired IP camera. Mounting kit.	

<sup>1</sup> Under development.

Contact us







**ELTEX** Enterprise is a leading Russian developer and manufacturer of communication equipment with 30 years of history. Complete solutions and their seamless integrability into the Customer's infrastructure are the priority growth areas of the company.

About ELTEX