

- Built-in microSD slot
- Built-in microphone
- Metal casing
- Support for PoE
- IR illumination up to 40 m
- Configuration via web interface
- ONVIF



**SV-BA314-E** wired IP camera with a dome design provides a horizontal viewing angle of 100° and is equipped with a 4 MP CMOS matrix for clear video with a resolution of up to 2560 × 1440. The device has a night shooting mode (IR illumination), motion detection system and the function of saving the video archive to a memory card or network storage<sup>1</sup>. The camera is equipped with an RJ-45 connector with support for basic network protocols.

## Technical features

### Interfaces

Ethernet	1 × 10/100BASE-T (RJ-45), support for PoE
Memory card	1 × MicroSD/SDHC/SDXC up to 256 GB

### Operating system

Linux SDK

### Sensor

Type	1/3" progressive scan CMOS
Effective pixels	4M

### Lens and illumination

Focal distance	2.8 mm
Aperture	F/2.0
Field of view (horizontal)	100°
Field of view (diagonal)	116°
Angle adjustment (tilt)	from 0° to 105°
Angle adjustment (rotate)	from 0° to 360°
IR illumination	yes
IR range	up to 40 m

### Image

Maximum resolution	2560 × 1440
Maximum frame rate	25 fps
Bit rate	up to 10 Mbps
Video compression	H.264, H.265
Image quality improvement	DNR 2D/3D, DWDR, BLC, AE, AWB, HLC, ANTI-FLICKER, DEFOG, ROI <sup>1</sup>
Signal-to-noise ratio	no less than 50 dB
Luminous sensitivity	color: 0.01 lx, bw: 0 lx with IR

<sup>1</sup> Under development.

**Technical features (continued)**

Audio	
Built-in microphone	yes
Audio compression	PCM, AAC, MP2, ADPCM <sup>1</sup> , G.711U (PCMU) <sup>1</sup> , G.711A (PCMA) <sup>1</sup> , G.726 <sup>1</sup>
Voice pickup distance	up to 5 m
Physical specifications	
Power supply	12 V DC, PoE 802.3af (Mode A) <sup>2</sup>
RAM	128 MB
ROM	32 MB
Casing	metal, plastic
Form factor	dome camera
Mount options	indoor and outdoor
Dimensions (Height × Diameter)	90 × 110 mm
Weight	0.39 kg
Operating temperature	from -40 to +60 °C
Operating humidity	no more than 90 % (non-condensing)
Ingress protection	IP67

**Analytics and protocols<sup>1</sup>**

- Face recognition
- Motion detection
- Human silhouette recognition
- Line crossing
- Perimeter intersection
- ONVIF (Profile S,T)

**Features and capabilities**

- Night vision
- Storage: memory card, network storage<sup>1</sup>
- Management via web interface
- Non-volatile time (up to 24 hours)

**Ordering information**

Name	Description
<b>SV-BA314-E</b>	SV-BA314-E wired IP camera. Mounting kit.

<sup>1</sup> Under development.<sup>2</sup> Does not support PoE Mode B (power supply over Pairs 4/5 and 7/8).**Contact us****About Eltex**

+7 (383) 274 10 01  
+7 (383) 274 48 48



eltex@eltex-co.ru



www.eltex-co.com

**Eltex Enterprise** is a leading Russian developer and manufacturer of communication equipment with 30 years of history. Complete solutions and their seamless integrability into the Customer's infrastructure are the priority growth areas of the company.