

- Built-in microSD slot
- Built-in microphone
- Metal casing
- Support for PoE
- IR illumination up to 30 m
- Configuration via web interface
- ONVIF



SV-BA401-E wired IP camera with a cylindrical design provides a horizontal viewing angle of 100° and is equipped with a 4 MP CMOS matrix for clear video with a resolution of up to 2560×1440 . The device has a night shooting mode (IR illumination), motion detection system and the function of saving the video archive to a memory card or network storage¹. The camera is equipped with an RJ-45 connector with support for basic network protocols.

Technical features

	Interfaces
Ethernet	$1 \times 10/100$ BASE-T (RJ-45), support for PoE
Memory card	1 × MicroSD/SDHC/SDXC up to 128 GB
	Operating system
Linux SDK	
	Sensor
Туре	1/3" progressive scan CMOS
Effective pixels	4M
	Lens and illumination
Focal distance	2.8 mm
Aperture	F/2.0
Field of view (horizontal)	100°
Field of view (diagonal)	116°
Angle adjustment (tilt)	from 0° to 90°
Angle adjustment (rotate)	from 0° to 360°
IR illumination	yes
IR range	up to 30 m
	Image
Maximum resolution	2560 × 1440
Maximum frame rate	25 fps
Bit rate	up to 10 Mbps
Video compression	H.264, H.265
Image quality improvement	BLC, HLC, DWDR, ANTI-FLICKER
Signal-to-noise ratio	no less than 50 dB
Luminous sensitivity	color: 0.03 lx, bw: 0 lx with IR

1 www.eltex-co.com

¹ Under development.



Technical features (continued)

	Audio	
Built-in microphone	yes	
Built-in dynamic	no	
Audio compression	PCM, AAC, MP2	
Voice pickup distance	up to 5 m	
Physical specifications		
Power supply	12 V DC, PoE 802.3af (Mode A) ¹	
RAM	128 MB	
ROM	32 MB	
Casing	metal	
Form factor	cylindrical camera	
Mount options	indoor and outdoor	
Dimensions (W \times H \times D)	70 × 67 × 186 mm	
Weight	0.38 kg	
Operating temperature	from -40 to +60 °C	
Operating humidity	no more than 90 % (non-condensing)	
Ingress protection	IP67	

Analytics and protocols²

- Motion detection
- Line crossing
- Perimeter intersection

Features and capabilities

- Night vision
- Storage: memory card, network storage²
- Management via web interface
- Non-volatile time (up to 24 hours)

Ordering information

Name	Description
SV-BA401-E	SV-BA401-E wired IP camera. Mounting kit.

¹ Does not support PoE Mode B (power over pairs 4/5 and 7/8).

Contact us About Eltex









Eltex Enterprise is a leading Russian developer and manufacturer of communication equipment with 30 years of history. Complete solutions and their seamless integrability into the Customer's infrastructure are the priority growth areas of the company.

² Under development.