

- Remote control
- Easy installation
- Motion detection
- Suitable for integrating operator software



SV-CA213-WE is a Wi-Fi camera designed for video monitoring of premises in real time. The high resolution provides a clear and high-quality image.



Technical features

Interfaces

| | |
|--------------------|----------------------------|
| Memory card | 1 × MicroSD |
| Ethernet interface | 1 × 10/100BASE-T (RJ-45) |
| Wireless network | IEEE 802.11a/b/g/n 2.4 GHz |

Operating system

| |
|-----------|
| Linux SDK |
|-----------|

Sensor

| | |
|------------|----------------------------|
| Type | 1/3" progressive scan CMOS |
| Resolution | 4 MP |

Lens and illumination

| | |
|----------------------------|-------------------------------------|
| Focal distance | 2.8 mm |
| Aperture | F/2.0 |
| Field of view (horizontal) | 100° |
| Field of view (diagonal) | 116° |
| Angle adjustment (tilt) | from 0° to 90° |
| Angle adjustment (rotate) | from 0° to 360° |
| IR illumination | yes |
| IR range | up to 5 m |
| Light sensor | yes |
| Minimum illumination | no more than 0.02 lux in color mode |

Technical features (continued)

| Image | |
|--------------------------------|--|
| Image | color |
| Maximum resolution | 2560 × 1440 |
| Maximum frame rate | 25 fps |
| Bit rate | up to 10 Mbps |
| Video compression | H.264, H.265 |
| Image enhancement | DNR 2D/3D, DWDR |
| Audio | |
| Built-in microphone | yes |
| Automatic gain control | yes |
| Noise-cancelling | yes |
| Signal to noise ratio | 60 dB |
| Built-in dynamic | yes |
| Audio compression format | PCM, AAC, MP2 |
| Voice pickup distance | up to 5 m |
| Physical specifications | |
| Hardware device version | 3v1 |
| Display | two-color (red, blue) |
| RTC chip | yes |
| Built-in battery life | 1 day |
| Power | power adapter with Type C connector 5 V, 2 A |
| RAM | 128 MB |
| ROM | 16 MB |
| Built-in memory type | NOR |
| Casing | plastic |
| Form factor | pan-tilt |
| Mount options | indoor |
| Dimensions (Diameter × Height) | 78 × 109 mm |
| Operating temperature | from 0 to +45 °C |
| Operating humidity | no more than 90 % (non-condensing) |

Features and capabilities

- Night vision
- Motion detection
- Video archive: to a memory card for local storage or to network storage¹.
- Non-volatile clock (up to 24 hours)

¹ Under development.

Ordering information

| Name | Description |
|-------------|--------------------------|
| SV-CA213-WE | SV-CA213-WE Wi-Fi camera |

Contact us



+7 (383) 274 10 01
+7 (383) 274 48 48



eltex@eltex-co.ru



www.eltex-co.com

About Eltex

Eltex Enterprise is a leading Russian developer and manufacturer of communication equipment with 30 years of history. Complete solutions and their seamless integrability into the Customer's infrastructure are the priority growth areas of the company.